

Fertilizer 32-0-4

Net Wt. 50 Lbs. (22.68 kg)

Contains Fortify-N[®]

Contains iron for improved turf color

Guaranteed Analysis

Total Nitrogen (N)	32.00%
32.00% Urea Nitrogen*	
Soluble Potash (K ₂ O)	4.00%
Iron (Fe)	2.00%
Plant nutrients derived from urea, potassium chloride and ferric oxide	

Chlorine (CI) Max.... 3.40%

*16.0% nitrogen stabilized with N-(n-butyl) thiophosphoric triamide F292

DIRECTIONS FOR USE Apply only as directed. Apply during the growing season.

Application Rates: LIGHT:

1.6 lbs/1,000 sq. ft. 2.3 lbs/1,000 sq. ft. 3.1 lbs/1,000 sq. ft. 3.9 lbs/1,000 sq. ft.

For all applications:

Apply to dry foliage.

- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to avoid particle pick-up.

Cool Season Grasses:

- Apply at the LOW or MEDIUM RATE.
- Apply at the LIGHT RATE when temperatures exceed 85°F.

Warm Season Grasses:

 Apply at the LOW to HIGH RATE every 4-6 weeks during the period of active growth.

Note: This product contains the micronutrient iron for extra greening and to help prevent iron deficiency. Iron may stain concrete and other surfaces. Misapplied product to these surfaces should be removed promptly by sweeping or blowing. DO NOT WASH OFF WITH WATER.

Recent research has shown that environmental buffers prevent pollutants from entering our natural water bodies. To help protect these natural resources, avoid applying product to sidewalks, driveways, roadways,

and other impervious surfaces. Sweep any misplaced granules back onto the area you are treating immediately after application, since storm drains often empty directly to nearby waterways.

STORAGE AND USE

Store in a clean, dry place.

Reseal opened bag by folding top down and securing. Use only in clean, dry spreaders.

Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consister with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS. Use contrary to label directions is not permitted.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of U.S.A.

The Andersons, Inc. P.O. Box 119 Maumee, OH 43537 www.andersonspro.com

Suggested Spreader Settings

These suggested spreader settings are not intended to replace calibration.

Please calibrate your spreader before applying product. 50 lbs. feeds 31,200 sq. ft. (0.72 acre) with 0.51 lbs. N/1,000 sq. ft. at the LIGHT RATE

50 lbs. feeds 21,700 sq. ft. (0.50 acre) with 0.74 lbs. N/1,000 sq. ft. at the LOW RATE 50 lbs. feeds 16,100 sq. ft. (0.37 acre) with 0.99 lbs. N/1,000 sq. ft. at the MEDIUM RATE 50 lbs. feeds 12,800 sq. ft. (0,29 acre) with 1,25 lbs. N/1,000 sq. ft. at the HIGH RATE

30 lbs. leeds 12,000 sq. it. (0.29 acre) with 1.25 lbs. W1,000 sq. it. at the filding hate								
			SPREADER SETTINGS					
SPREADER	GROUND SPEED	WIDTH OF COVERAGE	LIGHT RATE 1.6 lbs/1,000 sq. ft.	LOW RATE 2.3 lbs/1,000 sq. ft.	MEDIUM RATE 3.1 lbs/1,000 sq. ft.	HIGH RATE 3.9 lbs/1,000 sq. ft.		
Andersons Model 2000 / AccuPro 2000 (cone 4); Andersons 2000 SR / SR-2000 (cone 4)	3 mph	11 feet	J 1/2	K 1/4	L	М		
Scotts R-8, R-8A (cone 4)	3 mph	11 feet	l 1/4	J	K	L		
Lesco 020093 (pattern 0.25)	3 mph	8 feet	D	D 1/2	Е	F		
Lesco 705698 (pattern 0.25)	3 mph	8 feet	10	11	12	14		
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern II-C	4.5 mph	38 feet	4 1/2	5	5 1/2	6		
Vicon (03 Series)	4.5 mph	30 feet	19	23	27	31		





advice. Wash hands after handling. Use only outdoors or in well ventilated areas. Avoid breathing dust. If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. Store contains

If victim is alert and not convulsing, give one glass of water to dilute material, but



© 2015 The Andersons, Inc. The Andersons logo is a registered trademark of The Andersons, Inc. www.AndersonsPro.com

> APT32UFE5.1 APT32UFE5.1B