





Specifications

Western Excelsior manufactures Excel Straw Logs in addition to a full line of Rolled Erosion Control Products (RECPs). Excel Straw logs consist of 100% clean, weed free straw fiber matrix confined by a synthetic net to form a log of specific length and diameter. Excel Straw Logs are designed to reduce hydraulic energy and filter sediment laden flow in channels and on slopes. The logs are flexible to conform to the soil surface and are secured by staking. Excel Straw Logs can be ordered in custom lengths to meet specific job conditions.

Each Excel Straw Log is made in the USA and manufactured under Western Excelsior's Quality Assurance Program to ensure a continuous distribution of fibers and consistent dimensions. Log dimensions are provided in Table 1 and product characteristics are provided in Table 2. Installation instructions and performance data are available from Western Excelsior's Technical Support Division.

Table 1 - Specified Expected Values				
Diameter	10 ft (3.0 m) Length	20 ft (6.0 m) Length	25 ft (7.6 m) Length	
9 in (0.23 m)	14.0 lbs (6.4 kg)	28.0 lbs (12.7 kg)	35.0 lbs (15.9 kg)	
	1.4 lbs/ft (2.1 kg/m)	1.4 lbs/ft (2.1 kg/m)	1.4 lbs/ft (2.1 kg/m)	
	3.3 lbs/ft³ (52.3 kg/m³)	3.2 lbs/ft³ (51.6 kg/m³)	3.2 lbs/ft³ (51.5 kg/m³)	
12 in (0.31 m)	25.0 lbs (11.3 kg)	50.0 lbs (22.7 kg)	62.5 lbs (28.4 kg)	
	2.5 lbs/ft (3.7 kg/m)	2.5 lbs/ft (3.7 kg/m)	2.5 lbs/ft (3.7 kg/m)	
	3.3 lbs/ft³ (53.0 kg/m³)	3.2 lbs/ft³ (52.1 kg/m³)	3.2 lbs/ft³ (51.9 kg/m³)	
18 in (0.46 m)	35.0 lbs (15.9 kg)	70.0 lbs (31.8 kg)	87.5 lbs (39.7 kg)	
	3.5 lbs/ft (5.2 kg/m)	3.5 lbs/ft (5.2 kg/m)	3.5 lbs/ft (5.2 kg/m)	
	1.7 lbs/ft³ (33.5 kg/m³)	2.0 lbs/ft³ (32.7 kg/m³)	2.0 lbs/ft³ (32.5 kg/m³)	
20 in (0.51 m)	50.0 lbs (22.7 kg)	100.0 lbs (45.4 kg)	125.0 lbs (56.7 kg)	
	5.0 lbs/ft (7.4 kg/m)	5.0 lbs/ft (7.4 kg/m)	5.0 lbs/ft (7.4 kg/m)	
	2.4 lbs/ft³ (39.0 kg/m³)	2.4 lbs/ft³ (37.9 kg/m³)	2.3 lbs/ft³ (37.7 kg/m³)	

Table 2 - Netting			
Fiber Composition	100% Clean, Weed free Straw		
Netting	0.50" x 0.50" Heavy Duty Synthetic		
Configuration	Cylindrical with Closed Ends		
End Closure	Hog Ring or Tied		

^{*}All values shown measured at the time of manufacture.

The information contained herein may represent product index data, performance ratings, bench scale testing or other material utility quantifications. Each representation may have unique utility and limitations. Every effort has been made to ensure accuracy, however, no warranty is claimed and no liability shall be assumed by Western Excelsior Corporation (WEC) or its affiliates regarding the completeness, accuracy or fitness of these values for any particular application or interpretation. While testing methods are provided for reference, values shown may be derived from interpolation or adjustment to be representative of intended use. For further information, please feel free to contact WEC.