



RECOMMENDED APPLICATION:

Mixing one bag of Waste Cover to 75 gallons of water will provide 450 square feet of coverage in standard mechanical agitation spray on equipment. A fully loaded FINN LF 120 landfill unit can cover up to 7500 square feet, while the process to load and discharge the slurry takes less than one hour.

* LF120: The FINN LF120 was designed specifically for landfill use and can be towed behind any piece of heavy equipment. Use the LF120 to spray on ADC, odor and dust control products as well as a wide variety of materials for turf development and erosion control.

Other size models are also available.

DESCRIPTION:

FINN Waste Cover is an Alternative Daily Cover (ADC) manufactured from recycled paper and wood and containing polymers, an enzyme complex, and other proprietary ingredients. When mixed with water in a FINN landfill spray application machine, the black spray on slurry is applied to the "open face" forming a cement-like crust. Waste Cover helps to alleviate odors and breaks down garbage faster.

MEETS ASTM D4982-95:

Flammability Potential Screening Analysis of Waste

MEETS ASTM D6523-00:

Standard Guide for Alternative Daily Cover for sanitary landfills:

- Minimize Disease Vectors
- Control Leachate and Erosion
- Reduce Fire Hazard Potential
- Minimize Wind Blown Litter
- Reduce Noxious Odors.
- Provide an Aesthetic Appearance.
- Allow Accessibility Regardless of Weather

Biodegradable Non-Toxic Non-Flammable
Easy to load, mix and discharge.



SMARTER WAYS TO WORK

9281 LeSaint Drive • Fairfield, OH 45014-5457 • Phone (513) 874-2818 • Fax (513) 874-2914
Toll Free (800) 543-7166 • Parts (800) 229-8707 • E-mail: sales@finncorp.com
Customer Service/Warranty (888) 382-1966